

412TW-PA-15213



Adventures in Reliability: Heavily Censored Data

Todd G. Remund

4
1
2
T
W

AIR FORCE TEST CENTER
EDWARDS AFB, CA

May 12-14, 2015

Approved for public release ; distribution is unlimited.
412TW-PA-15213

AIR FORCE TEST CENTER
EDWARDS AIR FORCE BASE, CALIFORNIA
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE

REPORT DOCUMENTATION PAGE

*Form Approved
OMB No. 0704-0188*

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

1. REPORT DATE (12-05-2015)		2. REPORT TYPE Technical Presentation		3. DATES COVERED (From - To) May 12, 2015	
4. TITLE AND SUBTITLE Adventures in Reliability: Heavily Censored Data				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Todd G. Remund				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) AND ADDRESS(ES) 812 TSS/ENT Statistical Methods Group 307 E. Popson Ave Edwards AFB CA 93524				8. PERFORMING ORGANIZATION REPORT NUMBER 412TW-PA-15213	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) N/A				10. SPONSOR/MONITOR'S ACRONYM(S) N/A	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release A: distribution is unlimited.					
13. SUPPLEMENTARY NOTES CA: Air Force Test Center Edwards AFB CA CC: 012100					
14. ABSTRACT At times reliability data are recorded as exact failure times on systems. This is a trivial case that is handled usually by simple textbook analysis approaches. Many times, especially in the T&E community, all that is known regarding failures is that a certain number of events have been observed during a flight. These type of data are called 'interval data' and do not equate with exact failure times. Trivial analysis approaches can severely bias MTBF estimates and 'paint a pretty picture'. In this presentation statistical techniques for handling this data are discussed.					
15. SUBJECT TERMS Reliability, Censored Data, Data, MTBF, Failure					
16. SECURITY CLASSIFICATION OF: Unclassified			17. LIMITATION OF ABSTRACT None	18. NUMBER OF PAGES 10	19a. NAME OF RESPONSIBLE PERSON 412 TENG/EN (Tech Pubs)
a. REPORT Unclassified					19b. TELEPHONE NUMBER (include area code) 661-277-8615
Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39.18					



412th Test Wing



War-Winning Capabilities ... On Time, On Cost

**Adventures in Reliability:
Heavily Censored Data**



U.S. AIR FORCE

May 12-14, 2014

Todd G. Remund

812 TSS

661-277-6384

Approved for public release; distribution is unlimited.

412TW-PA No.:15213

Integrity - Service - Excellence



Flight Test Failure Data



- Best case is to observe right, left or interval censored data
 - Fails during a flight...that's all we know.
- Right:

- Left:

- Interval:

 - Interval data happens when multiple flights occur before a failure is observed.
- We will ignore intervals this time...maybe next time.



Rehash of Rocket Motor Data



Catastrophic Missile Failures During Launch

- 20,000 missiles in inventory.
- 1,940 field firings of the missile.
- From June 1997 to March 1998 there were 3 catastrophic failures of the motor.
- *Estimated service life = 20 years.*
- *Saw catastrophic failures at:*
 - *T = 8.5, 14.2, and 16.5 years.*

Olwell, D., Sorell, A. (2001), Annual Reliability and Maintainability Symposium.




Possible Failure Causes

How do we analyze this? ... →



- Believed Failure Mechanism (acc. to NSWC-IH):
 - Thermal cycling—caused propellant-to-case bondline AND/OR propellant-to-propellant bondline to fail.
 - Causes the surface area to increase and explosive ignition of propellant.



Motor
Crossection




→...With one of many models. Choose your Adventure



- **Probability Models:**
 - Exponential
 - Lognormal
 - Weibull
 - Logistic
 - Log Logistic
 - Rayleigh
 - Frechet
 - Normal
 - SEV
 - LEV
 - ...
- All have descriptions of why they are useful.
- Censoring ⇒ Model Fitting Difficulty
 - Use likelihood methods...
- *Which one should we use?*
- *Does it matter?*




Fitted Life Models *{Best is MIN(AIC)}*





Which model would you choose? Based on Reliability Estimation and CI's





Summary

412TW

- Stake holders on both sides of the fence may choose different models based on interests.
 - Uncertainty in decisions, or indecision.
 - Implies model selection uncertainty.
 - Somebody has to choose...unbiasedly.
 - What tool or method will they use?
- Who can justify their choice?
- MORE QUANTITATIVE RIGOR
 - More to come on this in the future...